



24" LCD display available. It has the function of adaptive LCD matrix backlight that allows to adjust to prevailing lighting conditions.

Mechanical properties

Manufacturer	ELLT
Supply voltage range	16.8÷36 V DC
Rated voltage	24 V DC
Energy consumption	Max 70 W
Exit ports	1x HDMI, 1x DP, 1x DVI or VGA
Audio	1x Audio line out Jack 3.5mm
Power connector	2-pin connector MATE-N-LOK male
Screen diagonal	24" (16:9)
Active area	527.04 mm x 296.46 mm
Maximum resolution	1920x1080 px
Luminance (cd / m ²)	1000 (min 700)
Contrast	1000:1

Technical parameters

Dimensions	562 mm ± 2 mm x 337.5 mm ± 2 mm x 60 mm ± 1 mm
Mounting hole spacing	562 mm ± 2 mm x 250 mm ± 1 mm (holes on the side edges)
Weight	7.13±0.45 kg
Working temperature	-25÷55°C
Storage temperature	-25÷55°C
Relative humidity	10÷90% (no condensation)
Screen protection	Laminated glass 2+2 mm
Coated with paint	Any color from the RAL palette
Level of security	IP54 (front), IP40 (back)



Standards

Norms	EN 50155, EN 45545-2, EN 50121-3-2
-------	------------------------------------

Available models:

ETLCD240DV1-1 – without PC with 300 mm wires

ETLCD240DV1-2 – without PC with connectors